



**Summit**  
**Self-Propelled Scissor Lifts**  
**Hydraulic Drive**

For further information on Standard Features & Options

**CALL 1300 623 622**











S0608EH 6m  
S0808EH 8m  
S0812EH 8m  
S1012EH 10m



S0608EH 8m  
S0808EH 10m  
S0812EH 10m  
S1012EH 12m

S0608EH 1.87m  
S0808EH 1.89m  
S0812EH 1.78m  
S1012EH 1.92m



	S0608EH	S0808EH	S0812EH	S1012EH
 S.W.L	380kg	230kg	450kg	320kg
S.W.L on extension	113kg	113kg	113kg	113kg
Max. occupants(indoor / outdoor)	2/1	2/0	2/2	2/1
 Working Height	8.0m	10.0m	10.0m	12.0m
Platform Floor Height	6.0m	8.0m	8.0m	10.0m
 Overall Length	2.48m	2.48m	2.48m	2.48m
Overall Width	0.81m	0.81m	1.15m	1.15m
Overall Height(Rails Up)	2.20m	2.32m	2.32m	2.40m
Overall Height(Rails Down)	1.87m	1.89m	1.78m	1.92m
Platform Size	2.27X0.81m	2.27X0.81m	2.27X1.12m	2.27X1.12m
Platform Extension Size	0.9m	0.9m	0.9m	0.9m
Ground Clearance(Stowed)	0.1m	0.1m	0.1m	0.1m
Ground Clearance(Raised)	0.019m	0.019m	0.019m	0.019m
Wheelbase	1.87m	1.87m	1.87m	1.87m
Turning Radius(Inside)	0m	0m	0m	0m
Turning Radius(Outside)	2.10m	2.10m	2.20m	2.20m
 Lifting/drive Motor	24V/3.3kw	24V/3.3kw	24V/3.3kw	24V/4.5kw
Travel Speed(Stowed)	3.5km/h	3.5km/h	3.5km/h	3.5km/h
Travel Speed(Raised)	0.8km/h	0.8km/h	0.8 km/h	0.8km/h
Up/down Speed	24/54sec	28/40sec	28/38sec	45/36sec
Wind Rated	12.5m/s	n/a	12.5m/s	12.5m/s
 Batteries	4X6V/225Ah	4X6V/225Ah	4X6V/225Ah	4X6V/240Ah
Integrated Charger	24V/25A	24V/25 A	24V/ 25 A	24V/25 A
 Gradeability	25%	25%	25%	25%
Maximum Working Slope	2° / 3°	1.5° / 3°	2° / 3°	2° / 3°
 Tyres	Φ381X127mm	Φ381X127mm	Φ381X127mm	Φ381X127mm
 Weight	2085kg	2140kg	2615kg	2945kg

\* Product specifications and prices are subject to change without notice or obligation  
The photographs and/or drawings in this document are for illustrative purposes only